

XYZ PROTURN RLX 555

SPINDLE 11.2 kW / (15 HP)
3 METRE GAP BED LATHE
SWING OVER BED 560 mm
SPINDLE BORE 104 mm
DISTANCE BETWEEN CENTRES 3,000 mm
MAX 1,800 RPM



	XYZ RLX 555- 3 metre
Swing over bed	560 mm
Swing in gap	935 mm
Gap in front of faceplate	297 mm max
Swing over cross slide	350 mm
Cross slide travel	290 mm
Distance between centres	3,000 mm
Maximum cutting length	2,900 mm
Spindle bore	104 mm
Spindle nose	D 1-11 camlock
Spindle taper	MT 7 in bush
Spindle motor	11.2 kW / (15 HP)
Spindle speeds	30-1,800 rpm (2 ranges)
Tailstock travel	200 mm
Tailstock taper	MT 6
Tailstock diameter	105 mm
Bed width	500 mm
Footprint L x D x H	5,300 x 2,010 x 1,840 mm
Weight	6,600 kg

Standard Equipment

315 mm 3 Jaw Chuck.
Constant Surface Speed.
TRAKing®.
2 Range Headstock.
Quick Change Toolpost with 6 Holders.
Rapid Traverse with Joy Stick.
Air Assist Tailstock.
Interlocked Chuck Guard and Main Guard.
Auto Lubrication.
Flood Coolant.
Worklight.
Centres and Bushes.

Optional Equipment

Advanced Features.
Verify Solid Model Graphics.
DXF File Converter.
Offline Programming.
Drilling Attachment.
Adjustable Back Stop.
Faceplates, Steadies, Chucks and Collet Chucks.
4 or 8 Station Auto Indexing Toolpost.
Swarf Conveyor.



Part of the **XYZ Turning Catalogue** which includes:
ProtoTRAK® Lathes.
Turning Centres.
XL Extra Large Lathes.
Oil Country Lathes.
Mobile Robotic Automation.
Manual Mills & Lathes.
Grinders.
Tooling & Accessories.



Visit www.xyzmachinetools.com or the YouTube channel to see the video.