

XYZ PROTURN RLX 780

NEW

SPINDLE 32 kW / (43 HP)
3 METRE GAP BED LATHE
SWING OVER BED 780 mm
SPINDLE BORE 160 mm
DISTANCE BETWEEN CENTRES 3,000 mm
MAX 1,300 RPM



	XYZ RLX 780-3 metre
Swing over bed	780 mm
Swing in gap	1,090 mm
Gap in front of faceplate	157 mm
Swing over cross slides	535 mm
Cross slide travel	430 mm
Distance between centres	3,000 mm
Maximum cutting length	2,900 mm
Spindle bore	160 mm
Spindle nose	A2-11
Spindle taper	MT 7 in bush
Spindle motor	32 kW / (43 HP)
Spindle speeds	20-1,300 rpm - 2 ranges
Tailstock travel	200 mm
Tailstock taper	MT 6
Tailstock diameter	105 mm
Bed width	500 mm
Footprint L x D x H	5,400 x 2,300 x 2,100 mm
Weight	8,600 kg

Standard Equipment

500 mm 3 Jaw Chuck.
Constant Surface Speed.
TRAKing®.
2 Range Headstock.
Quick Change Toolpost with 6 Holders.
Rapid Traverse with Joy Stick.
Air Assist Tailstock.
Interlocked Chuck Guard and Main Guard.
Auto Lubrication.
Flood Coolant.
Worklight.
Centres and Bushes.

Optional Equipment

Advanced Features.
Verify Solid Model Graphics.
DXF File Converter.
Offline Programming.
Drilling Attachment.
Adjustable Back Stop.
Faceplates, Steadies and Chucks.
8 Station Auto Indexing Toolpost.
Swarf Conveyor.



Part of the **XYZ Turning Catalogue** which includes:
ProtoTRAK® Lathes.
Turning Centres.
XL Extra Large Lathes.
Oil Country Lathes.
Mobile Robotic Automation.
Manual Mills & Lathes.
Grinders.
Tooling & Accessories.



Visit www.xyzmachinetools.com or the YouTube channel to see the video.